

## SnapBrite® High Voltage AC-LED Modules SRL230... Smart DoB Family

## Smart DoB -Bluetooth / IoT

- ✓ 2700K 5000K, Selectable-CCT
  - Reduces Inventory
  - Reduces Customer Returns
- ✓ 25W, 1950 to 2300 Lumens
- ✓ Direct Mains; 90 to 132 VAC
- ✓ Low Flicker Meets CEC T24 & IEEE-1798
- ✓ Driver on Board Cost/Reliability
- ✓ Simple Installation
- ✓ Low THD
- ✓ Bluetooth Controlled "Mesh Lamp App"
  - CCT Select Control
  - > Dimming Control
  - > Connect to Smartphones, Tablets, Other Wireless Enabled Devices

## Patent Protected Circuit-to-System

- ✓ Great for;
  - > Downlights
  - Flush Mounts
  - > Low Bay
  - > Area Lights

ETL Recognition; UL 8750, CSA; C22.2

- Samples Available Now
- \* Can Ship in USA or China
- Pricing Available on Request

Available CCTs	2700K	CRI	≥ 80
	3000K	THD	≤ 27
	4000K	System Efficacy @ 3000K	≥ 100 lm/W
	5000K	Life @ TC = 70°C	50K/Hrs.

25W; ~2,300 Lumens @ 3000K

In-Process:

